



3915 152ND ST NE | MARYSVILLE, WA 98271 | 1.800.827.3747

Product Overview

The Narkomed GS incorporates state-of-the-art electronics combined with a user friendly interface that claims extremely intuitive controls. The machine is equipped with a single monitor screen which provides volume, pressure and oxygen data. All monitored parameters and alarm messages are displayed on a bright, easy to read EL display.

The Narkomed GS is equipped with the AV2 which is a volume preset, time cycled and pressure limited ventilator. It is equipped with electronic timing, pneumatic circuitry and independent controls for frequency, I:E ratio, inspiratory flow rate, tidal volume and inspiratory pressure limit. The unit is also equipped with a back up battery that will operate the ventilator for a full 30 minutes.



DRÄGER® NARKOMED GS

Specifications:

Dimensions:

Height: 53 inches
 Width: 36 inches
 Depth: 27 inches
 Weight: 375 lb

Power Input:...120 VAC, 60Hz, 220-240 VAC 50Hz

Oxygen Monitoring

Range10 – 100%
 Resolution.....1 vol %
 Accuracy..... ± 3 vol %

Airway Pressure Monitoring

Range -10 – 125 cmH2O
 Resolution.....1 cmH2O

Accuracy:..... ± 3 cmH2O or ± 10% of reading
 whichever is higher

Tidal Volume Monitoring

Range.....0.2 – 50 L
 Resolution..... 0.1 L
 Accuracy.....10% or 0.1 L, whichever is higher

Ventilator

Frequency (breaths per minute).....1 – 99
 I:E Ratio.....4:1 – 1:4.5
 Inspiratory Flow.....10 – 100 l/min
 Tidal Volume.....50 – 1,500 ml